

# TASSELLO TCV

---

TCS TASSELLO TCV is a specific anchor for mechanically anchoring insulation panels on all types of masonry, bearing the ETA 08/0314 marking with categories A-B-C-D-E. Its shape makes it ideal in TCS SISTEMA PRO for mechanically fixing Rockwool Panels by eliminating the thermal bridge in the SISTEMA.

- Restoration
- Resistant
- Versatile
- Quick
- Reversible
- Easy
- Green Building
- Pollution Resistant
- Consolidating Treatment



---

## Features

Anchors for mechanical anchorage of insulation panels on all types of ETA-certified masonry in the various classes. For correct use during installation, please refer to the TCS SISTEMA PRO manual.

---

## Warnings

- Product for professional use.
- Do not modify the product.
- Store the product in a dry place, in the original unopened packaging.
- Consult safety data sheet before using the product.
- The data given correspond to the technical and applicative knowledge in our possession for an appropriate use of the product. We therefore recommend carrying out a prior practical test in order to check the suitability of the product for its intended use and consumption.
- Protect surfaces from atmospheric phenomena, sun, wind, rain and frost.
- Since our company is not the executor of the works and cannot directly intervene on site conditions and the methods of execution of the works, the indications given are to be considered indicative and general, and therefore not binding for the same.
- The company reserves the right to make any changes it deems necessary at any time and without prior notice.
- For further information and practical product demonstrations, please consult our technical service.
- Always refer to the latest versions of the technical data sheets available at [www.tcs-srl.it](http://www.tcs-srl.it).

## Dati Tecnici

**PRODUCT TYPE:** Expansion anchor with steel screw ETA 08-0314 for TCS SISTEMA PRO

---

**MATERIAL** Polypropylene PP with thermal break steel nail

---

**DIAMETER OF THE SCREW ANCHOR** 60 mm

---

**Cat. A Cement C12/15 EN 206-1** 0.4 kN

---

**Cat. A Cement C16/20 - C50/60 EN 206-1** 0.6 kN

---

**Cat. B Solid brickwork EN 771-1** 0.6 kN

---

**Cat. C Perforated brickwork EN 777-1** 0.5 kN

---

**Cat. D LAC LAC Lightweight concrete EN 1520** 0.5 kN

---

**Cat. E Cellular cement EN 771-4** 0.3 kN

---

**AVAILABLE LENGHT** diameter 8 mm - fastening from 110 mm to 310 mm

---

**PACKAGING** 100 pz

---

**STORAGE** In the original packaging in a dry place